

DSTS5 Dual Standard Test Set



The DSTS5 is a field test telephone featuring local battery operation, talk battery output and ringing current generation. The product is approved to EN 55022, Limit B and EN 55011.

- Super high impact case.
- Central or local battery operation.
- Allows the direct attachment of lines to give power.
- Timed break recall.
- Off line memory retention.
- Automatic monitor before loop operation.

Description	Cat./UPC No.
DSTS5 Dual Standard Test Set	M0068/00

Talk 2



Combined with any test telephone, the Talk 2 provides the functionality of the DSTS 5 providing a ring generator and talk battery. It operates over 3000 Ohms loop resistance.

Description	Cat./UPC No.
Talk 2	M0088/00
TXRX7 Headset (optional)	M0074/00



Optional headset available.

Remote Control Loop 100

Nautilus
range



The RCL100 is designed to enable single man operation and comprises a switch and a commander unit providing the user with total control of the loop circuit. Switching modes are: to the exchange, open circuit, loop, or loop-the-line. The RCL100 is designed to operate with the Tone Generator 600J (page 27) and the Tone Probe 500J (page 25). When used with the 600J a tone can be applied enabling it to be tested and brought into service from a remote location.

Description	Cat./UPC No.
RCL100	M0553/00